

Leica ScanStation P16

Because every detail matters



Easy-to-use

The Leica ScanStation P16 features an intuitive and user-friendly touch screen interface. The one-touch scan button and wizard style software guarantees an easy workflow and enable a fast data check in the field. Combined with WLAN remote control, the Leica ScanStation P16 can be operated by any handheld device.

Value for money

Its attractive price-performance ratio, worldwide support and quality service from Leica Geosystems result in a low cost of ownership and make the Leica ScanStation P16 the perfect solution for companies entering the laser scanning business.

Reduced downtime

The extremely durable new laser scanner performs even under the toughest environmental conditions, such as extreme temperatures ranging from -20°C to $+50^{\circ}\text{C}$ and complies with the IP54 rating for dust and water resistance.

Complete scanning solution

Leica Geosystems offers the new Leica ScanStation portfolio as an integrated part of a complete scanning solution including hardware, software, service, training and support. 3D laser scanner data can be processed in the industry's leading 3D point cloud software suite, which consists of Leica Cyclone stand-alone software, Leica CloudWorx plug-in tools for CAD systems and the free Leica TruView.

Leica ScanStation P16

Product specifications

| System Accuracy | |
|---|---|
| Accuracy of single measurement * | |
| Range accuracy | 1.2 mm + 10ppm over full range |
| Angular accuracy | 8" horizontal; 8" vertical |
| 3D position accuracy | 3 mm at 40 m |
| Target acquisition ** | Up to 40 m in post-processing software |
| Dual-axis compensator | Liquid sensor with real-time onboard compensation, selectable on/off, resolution 1", dynamic range ±5', accuracy 1.5" |

| Distance Measurement System | |
|--------------------------------------|--|
| Type | Ultra-high speed time-of-flight enhanced by Waveform Digitising (WFD) technology |
| Wavelength | 1550 nm (invisible) / 658 nm (visible) |
| Laser class | 1 (in accordance with IEC 60825:2014) |
| Beam divergence | < 0.23 mrad (FWHM, full angle) |
| Beam diameter at front window | ≤ 3.5 mm (FWHM) |
| Range and reflectivity | Up to 40 m; 18% reflectivity (minimum range 0.4 m) |
| Scan rate | Up to 1'000'000 points per second |
| Range noise * | 0.4 mm rms at 10 m 0.5 mm rms at 40 m |
| Field-of-View | |
| Horizontal | 360° |
| Vertical | 290° |
| Data storage capacity | 256 GB internal solid-state drive (SSD) or external USB device |
| Communications/ Data transfer | Gigabit Ethernet, integrated Wireless LAN or USB 2.0 device |
| Onboard display | Touchscreen control with stylus, full colour VGA graphic display (640×480 pixels) |
| Laser plummet | Laser class 1 (IEC 60825:2014) Centring accuracy: 1.5 mm at 1.5 m Laser dot diameter: 2.5 mm at 1.5 m Selectable ON/OFF |

| Imaging System | |
|------------------------|---|
| Internal camera | |
| Resolution | 4 megapixels per each 17°×17° colour image; 700 megapixels for panoramic image |
| Pixel size | 2.2 µm |
| Video | Streaming video with zoom; auto-adjusts to ambient lighting |
| White balancing | Sunny, cloudy, warm light, cold light, custom |
| HDR | Tonemapped / full range |
| External camera | Canon EOS 60D and 70D supported |

| Power | |
|---------------------|--|
| Power supply | 24 V DC, 100 – 240 V AC |
| Battery type | 2× Internal: Li-Ion; External: Li-Ion (connect via external port, simultaneous use, hot swappable) |
| Duration | Internal > 5.5 h (2 batteries) External > 7.5 h (room temp.) |

| Environmental | |
|------------------------------|---|
| Operating temperature | -20°C to +50°C / -4°F to 122° F |
| Storage temperature | -40°C to +70°C / -40°F to 158° F |
| Humidity | 95%, non-condensing |
| Dust/Water | Solid particle/liquid ingress protection IP54 (IEC 60529) |

| Physical | |
|---------------------------|---|
| Scanner | |
| Dimensions (D×W×H) | 238 mm × 358 mm × 395 mm / 9.4" × 14.1" × 15.6" |
| Weight | 12.25 kg / 27.0 lbs, nominal (w/o batteries) |
| Battery (internal) | |
| Dimensions (D×W×H) | 40 mm × 72 mm × 77 mm / 1.6" × 2.8" × 3.0" |
| Weight | 0.4 kg / 0.9 lbs |
| Mounting | Upright or inverted |

| Control Options | |
|--|--|
| Full colour touchscreen for onboard scan control. | |
| Remote control: Leica CS10/CS15/CS20/CS35 controller or any other remote desktop capable device, including iPad, iPhone and other Smartphones; external simulator. | |

| Functionality | |
|--------------------------------|--|
| One button scan control | Scanner operation with one button concept |
| Scan area definition | Scan area selection from video or scan; batch job scanning |

| Ordering Information | |
|--|--|
| Contact your local Leica Geosystems representative or an authorised Leica Geosystems dealer. | |

All specifications are subject to change without notice.
All accuracy specifications are one sigma unless otherwise noted.
* At 78% albedo
** Algorithmic fit to planar HDS 4.5" B&W targets

Scanner: Laser class 1 in accordance with IEC 60825:2014
Laser plummet: Laser class 1 in accordance with IEC 60825:2014

iPhone and iPad are trademarks of Apple Inc.

Illustrations, descriptions and technical specifications are not binding. All rights reserved.
Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland 2016.
835466en - 04.16



Leica ScanStation P30/40



Leica Cyclone REGISTER



Leica Cyclone MODEL

Scan here to view
the online brochure!



Leica Geosystems AG
Heerbrugg, Switzerland

scanstation.leica-geosystems.com

active >>
Customer Care

Your Trusted Active Customer Care

Active Customer care is a true partnership between Leica Geosystems and its customers. Customer Care Packages (CCPs) ensure optimally maintained equipment and the most up-to-date software to deliver the best results for your business. The myWorld@Leica Geosystems customer portal provides a wealth of information 24/7.

- when it has to be **right**

Leica
Geosystems